

FINE FISSURED Ceramaguard / medium texture




FINE FISSURED Ceramaguard with PeakForm 24mm Exposed Tee grid

Armstrong Grid Options with FINE FISSURED



FINE FISSURED Ceramaguard with PeakForm 24mm Exposed Tee grid



Square Lay-in with Peakform Grid



green building council australia
MEMBER



FINE FISSURED Ceramaguard / medium texture



Sustainable Performance

- Green Star points may also be achieved using Armstrong ceilings (contact your Armstrong office for details).
- Recycled Content 42%

Key Selection Attributes

- Nondirectional visual reduces installation time and scrap
- Guaranteed resistance to chemical fumes and scrubbing
- Durable Scrubbable Washable
- **HumiGuard Max** performance – Sag-resistant formulation to withstand chemical fumes and extreme temperatures up to 49°C (including steam up to 135°C) and relative humidity up to 100%, including standing water applications

- Warranty: 30 years for **FINE FISSURED Ceramaguard HumiGuard Max** with Armstrong grid systems

30-Year System Performance Guarantee

Against Visible Sag
HumiGuard® Max

Against Mold/Mildew & Bacterial Growth
BioBlock™ Plus

Typical Applications

- Laboratories
- Locker rooms, shower areas
- Indoor pools
- Outdoor soffits and canopies
- Parking garages
- Hydrotherapy
- Exterior Soffits (see note under Application Considerations)
- Marine Use

Visual Selection

Performance Selection

Grid Face	Edge Profile	Item Number	Dimensions	Acoustics		Anti-Mold/ Mildew	Sag Resist	Light Reflect	Installed Cost
				NRC	CAC				
FINE FISSURED Ceramaguard									
24mm	Square lay-in	607M6	600 x 600 x 15mm	0.55	38			0.82	\$\$\$
		608M6	600 x 1200 x 15mm	0.55	40			0.82	\$\$\$



• Additional information on FINE FISSURED Ceramaguard and other Armstrong products can be found on our web site: www.armstrongceilings.com.au



Physical Data

Material
Ceramic and mineral fiber composite

Surface Finish
Scrubable factory-applied vinyl plastic paint with BioBlock™ mold/mildew inhibitor

Flame Spread/Fire Resistance
Conforms to BCA Spec. C1.10 and tested to AS/NZS 3837: 1998 – "Group 1" AS/NZS 1530.3

Thermal Resistance
R Value: 0.25 m²K/W

Backloading Recommendation
Contact your local Armstrong representative

Anti Mold / Mildew & Bacteria
"BioBlock™ Plus" contains an antimicrobial treatment, providing guaranteed resistance against growth of mold/mildew and Gram-positive and Gram-negative odour/stain causing bacteria for 30 years.

Weight
(6.86 kgs/m²)

Warranty
10-year limited warranty;
30-year with **HumiGuard Max** products and Armstrong hot dipped galvanised grid

Recommended Suspension Systems
PeakForm XL 24mm Exposed Tee grid
"Quick Lock™" Extruded Aluminium Tee grid with stainless steel joining components and suspension wire – for use over swimming pools and other wet/corrosive environments

Application Considerations
For Exterior soffit and marine applications, wind uplift should be considered

Addresses

AUSTRALIA

Brisbane (QLD/NT)
Telephone: (617) 3809 5565
Facsimile: (617) 3809 5507

Melbourne (VIC/TAS)
Telephone: (613) 9580 9633
Facsimile: (613) 9587 5139

Sydney (NSW)
Telephone: (612) 9748 1588
Facsimile: (612) 9748 8449

P R CHINA

Beijing
Telephone: (8610) 6510 2818
Facsimile: (8610) 6510 2821

Guangzhou
Telephone: (8620) 8375 3862
Facsimile: (8620) 8375 3861

Hong Kong
Telephone: (852) 2585 7800
Facsimile: (852) 2598 7113

Shanghai
Telephone: (8621) 6391 3366
Facsimile: (8621) 6391 3399

INDONESIA / PHILIPPINES

Telephone: (65) 6358 1083
Facsimile: (65) 6358 1084

MALAYSIA

Telephone: (603) 9131 8335
Facsimile: (603) 9131 8335

SINGAPORE

Telephone: (65) 6358 1082
Facsimile: (65) 6358 1084

TAIWAN

Telephone: (8862) 2786 7258
Facsimile: (8862) 2786 7259

THAILAND

Telephone: (662) 556 0585
Facsimile: (662) 556 0585