

ERIS RH95




ERIS RH95 1200 x 600mm with PeakForm 24mm Exposed Tee Grid

Armstrong Grid Options with ERIS RH95



ERIS Square Edge with PeakForm 24mm Exposed Tee Grid



Square Lay-in with Peakform Grid

New Technology	
15-Year System Performance Guarantee Against Visible Sag HumiGuard® RH95	
Against Mold/Mildew & Bacterial Growth BioBlock™ Plus	



ERIS RH95



Sustainable Performance

- Green Star points may also be achieved using Armstrong ceilings (contact your Armstrong office for details).
- Recycled Content 52%
- Fully Recyclable at end of life.

Key Selection Attributes

- **HumiGuard RH95** performance – Sag-resistant formulation to withstand chemical fumes and extreme temperatures up to 49°C and relative humidity up to 95%
- **BioBlock™** paint on face and back of HumiGuard panels to inhibit or retard growth of mold/mildew on painted surface
- Economical, easy to install and easy maintenance
- Non-directional visual reduces installation time and waste

New Technology

15-Year System Performance Guarantee
Against Visible Sag
HumiGuard® RH95

Against Mold/Mildew & Bacterial Growth
BioBlock™ Plus

Typical Applications

- Office area
- Retail
- Healthcare spaces
- Public areas
- Education

Visual Selection

Performance Selection

Grid Face	Edge Profile	Item Number	Dimensions	Acoustics		Anti-Mold/ Mildew	Sag Resist	Light Reflect	Installed Cost
				NRC	CAC				
ERIS RH95									
24mm	Square lay-in	3741	600 x 1200 x 9mm	0.45	0.45H			0.82	\$



green building council australia
MEMBER

- Additional information on ERIS RH95 and other Armstrong products can be found on our web site: www.armstrongceilings.com.au



Sag Resistant/
Humidity



Recycled



Mold Resistant



Pattern Available
Globally



Relative
Installed
Cost
SSSS / highest pricing
\$ / lowest pricing

Physical Data

Material
Wet-formed mineral fiber

Surface Finish
Factory-applied vinyl latex paint with BioBlock™ mold/mildew inhibitor

Flame Spread/Fire Resistance
Conforms to BCA Spec. C1.10 and tested to AS/NZS 3837: 1998 – “Group 1” AS/NZS 1530.3

Thermal Resistance
R Value: 0.17 m²K/W

Anti Mold / Mildew & Bacteria
“BioBlock™ Plus” contains an antimicrobial treatment, providing guaranteed resistance against growth of mold/mildew and Gram-positive and Gram-negative odour/stain causing bacteria for 15 years.

Weight
(2.64 kgs/m²)

Warranty
10-year limited warranty;
15-year with **HumiGuard** products and Armstrong hot dipped galvanised grid

Recommended Suspension Systems
24mm PeakForm Prelude Exposed Tee grid system

Addresses

AUSTRALIA

Brisbane (QLD/NT)
Telephone: (617) 3809 5565
Facsimile: (617) 3809 5507

Melbourne (VIC/TAS)
Telephone: (613) 9580 9633
Facsimile: (613) 9587 5139

Sydney (NSW)
Telephone: (612) 9748 1588
Facsimile: (612) 9748 8449

P R CHINA

Beijing
Telephone: (8610) 6510 2818
Facsimile: (8610) 6510 2821

Guangzhou
Telephone: (8620) 8375 3862
Facsimile: (8620) 8375 3861

Hong Kong
Telephone: (852) 2585 7800
Facsimile: (852) 2598 7113

Shanghai
Telephone: (8621) 6391 3366
Facsimile: (8621) 6391 3399

INDONESIA / PHILIPPINES

Telephone: (65) 6358 1083
Facsimile: (65) 6358 1084

MALAYSIA

Telephone: (603) 9131 8335
Facsimile: (603) 9131 8335

SINGAPORE

Telephone: (65) 6358 1082
Facsimile: (65) 6358 1084

TAIWAN

Telephone: (8862) 2786 7258
Facsimile: (8862) 2786 7259

THAILAND

Telephone: (662) 556 0585
Facsimile: (662) 556 0585